Server Error in '/' Application.
___

Timeout expired. The timeout period elapsed prior to obtaining a connection from the pool. This may have occurred because all pooled connections were in use and max pool size was reached.

Description: An unhandled exception occurred during the execution of the current web request. Please review the stack trace for more information about the error and where it originated in the code.

Exception Details: System.Exception: Timeout expired. The timeout period elapsed prior to obtaining a connection from the pool. This may have occurred because all pooled connections were in use and max pool size was reached.

Source Error:

```
The source code that generated this unhandled exception can only be shown when compiled in debug mode. To enable this, please follow one of the below steps, then request the URL:

1. Add a "Debug=true" directive at the top of the file that generated the error. Example:

  <%@ Page Language="C#" Debug="true" %>

or:

2) Add the following section to the configuration file of your application:

<configuration>
   <system.web>
       <compilation debug="true"/>
   </system.web>
</configuration>

Note that this second technique will cause all files within a given application to be compiled in debug mode. The first technique will cause only that particular file to be compiled in debug mode.

Important: Running applications in debug mode does incur a memory/performance overhead. You should make sure that an application has debugging disabled before deploying into production scenario.
```

Stack Trace:

```
[Exception: Timeout expired.  The
timeout period elapsed prior to
obtaining a connection from the
pool.  This may have occurred
because all pooled connections
were in use and max pool size was
reached.]

Ektron.Cms.Controls.ContentBlock.Fi
ll() +1423

Ektron.Cms.Controls.EkWebControl.On
Init(EventArgs e) +319

System.Web.UI.Control.InitRecursive
(Control namingContainer) +186

System.Web.UI.Control.AddedControl(
Control control, Int32 index) +189

Layouts_Page_Style_1.Load_Content_M
ain(CustomAttributeList
EktronAttributeList, String
Form_ID, String calendar_id,
String Content_ID, DataSet ds)
+446

Layouts_Page_Style_1.Page_Load(Obje
ct sender, EventArgs e) +740

System.Web.UI.Control.LoadRecursive
() +71

System.Web.UI.Page.ProcessRequestMa
in(Boolean
includeStagesBeforeAsyncPoint,
Boolean
includeStagesAfterAsyncPoint)
+3178
```